

## NEUTRA CLEAN

**NEUTRA CLEAN** is an enzyme based cleaner that effectively removes trace contaminants and soils that prevent **NEUTRA RUST** products from properly adhering to substrates. It can be used in a wide range of temperatures and on any surface not harmed by water.

**NEUTRA CLEAN** is highly concentrated and biodegradable, making it both cost effective and environmentally friendly. This non-toxic formulation is also an employee safe solution in place of harsh cleaners.

**NEUTRA CLEAN** is an excellent choice to use as a follow up cleaner after a surface is degreased using **NEUTRA SOLV**. It can also be used in place of harsh detergents to clean lightly soiled surfaces prior to application of any coating.

**NEUTRA CLEAN** contains specially stabilized and blended enzymes that digest organic waste materials and allow them to be rinsed away. **NEUTRA CLEAN** allows you to eliminate these organic accumulations in an environmentally responsible way. This combination of mild surfactants and biological agents allows for quicker soil release.

### PHYSICAL PROPERTIES:

<b>COLOR</b>	Pale amber
<b>FRAGRANCE</b>	Mild
<b>APPLICATION</b>	Pressure wash, spray, mop rag, any cleaning method
<b>DILUTION</b>	Up to 20:1 with water
<b>pH</b>	6.5-7.5
<b>SPECIFIC GRAVITY</b>	1.02
<b>ENZYMES</b>	Protease, amylase, uricase, lipase/esterase, beta-glucanase

### APPLICATION NOTES:

Remove old, heavy deposits of grease, oil, tar, soot and other contaminants with a solvent cleaner. (We recommend **NEUTRA SOLV**) Thoroughly wet surface to be cleaned. Apply appropriate dilution of **NEUTRA CLEAN**. Let the surface soak for 5-7 minutes. Do not allow product to dry. Rinse under high pressure if possible. Rinse thoroughly, then apply the appropriate **NEUTRA RUST** coating product.

**NEUTRA CLEAN** can be used at temperatures ranging from 40 to 140 F.

Store **NEUTRA CLEAN** in cool areas (under 100 F) to achieve maximum shelf life. Keep container closed tightly.

This information given on these product data sheets is based upon tests believed to be accurate at the time of printing. Since we have no control over the specific working conditions, materials involved and circumstances under which the purchaser stores, handles or uses this material, we make no warranty or condition, either express or implied with respect to this material. We reserve the right to alter any of the foregoing information at any time without prior notice.

Corrosion Control Industries  
P.O. Box 540, Johnson City, TN 37605  
Tel 423-232-6255  
Fax 423-232-6256  
Toll free 877 661 RUST (7878)  
www.neutrarustinc.com  
www.sundancegrp.com

Distributed by: Sundance Group, Inc.  
P.O. Box 540  
Johnson City, TN 37605